

Model Specific Information

Thank you for purchasing an ALWAYS Bikes electric bicycle. We are proud to provide a quality product that will provide an un-paralleled ownership and riding experiences for years.

Please note the following information will highlight specification, anatomy of your bike, and geometry.

If you have questions after reading this manual, please refer to ALWAYS Bikes Online Support.

eBliss Global, Inc. dba ALWAYS BIKES

<https://www.ALWAYSBikes.com/support>

eMail questions to support@alwaysbikes.com

Call Toll Free at 888-341-6450



OUTA'HERE

SPEC



Class III	65+ Miles	48V 14Ah UL2271 Compliant
<i>Classification</i>	<i>Range TRIP/PAS/PEDAL</i>	<i>Battery</i>
750W 80Nm REAR HUB UL2849 Compliant	672 Wh	28mph TRIP/PAS 20mph Throttle
<i>Motor Size</i>	<i>Wh- Watt Hours</i>	<i>Top Speed</i>
BAFANG 2 speed Rear HUB	Triple Sensor Technology Torque, Cadence, Speed	68 lbs.
<i>Gearing</i>	<i>Sensor</i>	<i>Bike Weight</i>
Belt Driven	300 lbs	Black/Aqua or Black/Red
<i>Drive</i>	<i>Max Pay Load Capacity</i>	<i>Color Options</i>

<i>Rider Fit</i>	5' 6" to 6'2" Top Tube
<i>Frame Material</i>	6061 Aluminum
<i>Brakes</i>	Hydraulic Disc Brakes w/180mm Rotor
<i>Tire Size</i>	26" x 4.8" pressure 15-40 PSI (ideal 15 PSI)
<i>Charging Time</i>	4-5 hours
<i>Charger Input/Output</i>	100-240V 50/60Hz AC - 54.6V 3A DC-CE certified, UL listed
<i>IP level</i>	IPX4
<i>Accessories Included</i>	Bell, Kickstand

OUTA'HERE

ANATOMY



BAFANG
2spd REAR
HUB MOTOR



OUTA'HERE

GEOMETRY



			OUTA'HERE
B	Wheel- Base	mm	1219
C	Front Center	mm	736
D	Chain Stay	mm	489
E	Bottom Bracket (BB) Height	mm	325
F	Seat Tube Length	mm	432
G	Seat Tube Angle	deg	73
H	Head Tube Length	mm	140
I	Head Tube Angle	deg	68
J	Frame Stack	mm	602
K	Frame Reach	mm	465
L	Effective Top Tube Length	mm	650